Tableaux de tolérances VR Trade

Plaques et bandes en caoutchouc
DIN 7715 partie 5

Largeur/longueur

De (mm)	Jusqu'à inclus (mm)	P2 (mm)
0	±1.60	±0.20
±1.60	4	±0.30
4	±6.30	±0.40
±6.30	10	±0.50
10	25	±0.60
25	40	±0.80
40	63	±1.00
63	100	±1.20
100	160	±1.40
160	250	±1.60
250	400	±2.50
400	–	±0,8 %

Épaisseur

De (mm)	Jusqu'à inclus (mm)	P2 (mm)
0	1.6	±0.20
1.6	4	±0.30
4	6.3	±0.40
6.3	10	±0.50
10	25	±0.60
25	40	±0.80
40	63	±1.00
63	100	±1.20

The General Conditions of VR TRADE BV are applicable to all offers, agreements and deliveries of VR TRADE BV. The General Conditions will be sent to you on request and can be consulted on our website www.vrtrade.nl.

Profilés extrudés

DIN 7715 partie 3 / DIN ISO 3302-1 (classe E)

De (mm)	Jusqu'à inclus (mm)	E2 (mm)
0	±1.50	±0.25
±1.50	±2.50	±0.35
±2.50	±4.00	±0.40
±4.00	±6.30	±0.50
±6.30	10	±0.70
10	16	±0.80
16	25	±1.00
25	40	±1.30
40	63	±1.60
63	100	±2.00

The General Conditions of VR TRADE BV are applicable to all offers, agreements and deliveries of VR TRADE BV. The General Conditions will be sent to you on request and can be consulted on our website www.vrtrade.nl.