Tolerance tables VR Trade

Rubber sheeting and strips
DIN 7715 part 5

Width/length

From (mm)	Up to and including (mm)	P2 (mm)
0	±1.60	±0.20
±1.60	4	±0.30
4	±6.30	±0.40
±6.30	10	±0.50
10	25	±0.60
25	40	±0.80
40	63	±1.00
63	100	±1.20
100	160	±1.40
160	250	±1.60
250	400	±2.50
400	–	±0.8 %

Thickness

From (mm)	Up to and including (mm)	P2 (mm)
0	1.6	±0.20
1.6	4	±0.30
4	6.3	±0.40
6.3	10	±0.50
10	25	±0.60
25	40	±0.80
40	63	±1.00
63	100	±1.20

The General Conditions of VR TRADE BV are applicable to all offers, agreements and deliveries of VR TRADE BV. The General Conditions will be sent to you on request and can be consulted on our website www.vrtrade.nl.

Extruded profiles

DIN 7715 part 3 / DIN ISO 3302-1 (class E)

From (mm)	Up to and including (mm)	E2 (mm)
0	±1.50	±0.25
±1.50	±2.50	±0.35
±2.50	±4.00	±0.40
±4.00	±6.30	±0.50
±6.30	10	±0.70
10	16	±0.80
16	25	±1.00
25	40	±1.30
40	63	±1.60
63	100	±2.00

The General Conditions of VR TRADE BV are applicable to all offers, agreements and deliveries of VR TRADE BV. The General Conditions will be sent to you on request and can be consulted on our website www.vrtrade.nl.